



# Saving Rain LLC

## Installation Instructions for the Rainwater Diverter Box

Step 1: Determine the placement of the diverter box. In any downspout position the diverter box higher than the rain barrel or water collection unit. .



Step 2: Cut out a 5" section of the existing downspout. Mark the position on your structure & downspout where you want the diverter box to be inserted, take down the downspout and cut with a hacksaw. Be very careful using sharp tools.

Mark the bottom position on structure



Step 3: Using the marked position for the lower portion of your downspout, fasten a gutter strap to your structure below the guideline using the longer screw provided.



step 4: Position the lower portion of the downspout on the strap that is secured to your structure. Wrap the band tightly around the downspout. Position the chute in the bottom of the diverter box into the downspout and secure the strap, downspout, and diverter box with the short screw provided.



Step 5: Place a downspout band in the center of the top lip of the diverter box. Using the longer screw provided, screw through the band and the lip of the diverter box into your structure. If you are concerned with moisture entering any of the screw entry holes in your building, put a dab of silicone sealer on the area.



Step 6: Position the upper portion of your downspout over the band, wrap the band tightly around the downspout and screw together.

Step 7: Insert the filter into the diverter box and connect the hoses to the cylinders if not already done. Connect the other end of the hoses to your water collection unit or divert to a rain garden, and wait for it to rain! We do recommend additional gutter filters to catch most of the large debris before it comes down the downspout.



### WINTERIZATION OR WHEN NOT IN USE

If you do not wish to use both cylinders, one of them may be plugged at any time. Remove the filter screen and plug the cylinders with the rubber plugs provided. **Rubber plugs are attached to your filter screen-just unscrew and use. Remove the filter for winter in northern regions.**